

Heat Pumps ecoGEO_Compact 5-22

| | | C1 5-22 | C2 5-22 | C3 5-22 | C4 5-22 |
|---------------------------|---|---------|--------------|--------------|--------------|
| Application | Heating | ✓ | ✓ | ✓ | ✓ |
| | DHW with integrated storage tank, 165 l | ✓ | ✓ | ✓ | ✓ |
| | Integrated active cooling | | | ✓ | ✓ |
| | Integrated passive cooling | | | ✓ | ✓ |
| | Passive outdoor cooling control | | ✓ | | ✓ |
| Performance | Compressor range of modulation | % | 25 to 100 | 25 to 100 | 25 to 100 |
| | Heating power, B0W35 | kW | 6 to 25 | 6 to 25 | 6 to 25 |
| | COP, B0W35 max. | - | 4.9 | 4.9 | 4.9 |
| | Active cooling power, B35W7 | kW | | 7 to 29 | 7 to 29 |
| | EER, B35W7 max. | - | | 5 | 5 |
| | Passive cooling power, B16W19 / B16W23 | kW | | 4 / 9.3 | 4 / 9.3 |
| | Maximum unassisted storage temperature | °C | 58 | 58 | 58 |
| | Unassisted DHW heating rate | °C/min | 1.9 | 1.9 | 1.9 |
| | Maximum assisted storage temperature | °C | 70 | 70 | 70 |
| | Noise emission level | db | 35 to 46 | 35 to 46 | 35 to 46 |
| Operation limits | Energy Label/ η_s with average temperature control | | | A+++ / 206% | |
| | Heating outlet temperature | °C | 20 to 60 | 20 to 60 | 20 to 60 |
| | Cooling outlet temperature | °C | 4 to 35 | 4 to 35 | 4 to 35 |
| | Brine inlet temperature | °C | -10 to 35 | -10 to 35 | -10 to 35 |
| | Cooling circuit pressure | bar | 2 to 45 | 2 to 45 | 2 to 45 |
| | Production circuit pressure | bar | 0.5 to 3 | 0.5 to 3 | 0.5 to 3 |
| | Brine circuit pressure | bar | 0.5 to 3 | 0.5 to 3 | 0.5 to 3 |
| | Maximum DHW storage tank pressure | bar | 8 | 8 | 8 |
| | Refrigerant type / load | kg | R410A/1.70 | R410A/1.70 | R410A/2.00 |
| | Compressor oil type / load | kg | POE/1.18 | POE/1.18 | POE/1.18 |
| Electrical data: 230 V | Recommended protection | A | C40A | C40A | C40A |
| | Maximum consumption, B0W35 | kW/A | 5.8/25.2 | 5.8/25.2 | 5.8/25.2 |
| | Maximum consumption, B0W55 | kW/A | 8.5/36.8 | 8.5/36.8 | 8.5/36.8 |
| | Starting current | A | 11.1 | 11.1 | 11.1 |
| | Correction of cosine φ | - | 0.96-1 | 0.96-1 | 0.96-1 |
| Electrical data: 400 V | Maximum recommended external protection | A | C16A | C16A | C16A |
| | Maximum consumption, B0W35 | kW/A | 5.8/8.4 | 5.8/8.4 | 5.8/8.4 |
| | Maximum consumption, B0W55 | kW/A | 8.5/12.2 | 8.5/12.2 | 8.5/12.2 |
| | Starting current | A | 3.7 | 3.7 | 3.7 |
| | Correction of cosine φ | - | 0.96-1 | 0.96-1 | 0.96-1 |
| Dimensions and weight | Height x width x depth | mm | 1804x600x710 | 1804x600x710 | 1804x600x710 |
| | No-load weight with desuperheater | kg | 247 | 255 | 247 |

